

ACSX-1 HIGH PROFILE POWER CONNECTION KIT



The Ω HTS ACSX-1 Heat Trace Power Connection Kit is a CSA/(CUS) certified component for installation with Ω HTS's Self-Regulating Heating Cables – LXR, MXR & HXR. The ACSX-1 connects a Ω HTS Heater Cable to power and consists of a pipe mounted Stanchion and a J-Box complete with a DIN rail mounted terminal blocks.



The Stanchion provides excellent mechanical protection for heater cables installed on a pipe and permits application of up to 4" of thermal insulation. The J-Box provides ample room for installers to manipulate the heating cable and power wires. Grounding of the Heating Cable is achieved quickly and easily with no requirements for "pig-tailing" the ground braid. Hot work permits are not required to install the ACSX-1 due to the cold-applied core sealer supplied with the kit.

Specifications

Heating Cables	LXR, MXR, HXR
Enclosure Ingress Protection Rating	NEMA 4X, IP 66
Minimum Installation Temperature	-40°C/-40°F
Maximum Pipe Temperature	260°C/500°F
Maximum/Minimum Conductor Size	22 -8 AWG
Minimum Operating Temperature	-50° C/-60°F
Circuit Breaker Rating (Amps, Max.)	50 A
Maximum Operating Voltage	22 VAC

Ground-Fault Protection: Global Electric Codes require ground-fault

protection of each heating cable branch circuit to reduce the danger of fire caused by continuous electrical arcing resulting from improper installation or damage to the heating cable.

Conventional

circuit protection may not be suitable for preventing electrical arcing.

The following electronic heat trace controllers offer electronic

ground-fault protection: MS-2101, MS-2102 & MS-10 and/or ground-

fault circuit breakers or equivalent will satisfy this equipment

protection requirement: Square D Type QOB-EPD, or QO-EPD and

Cutler Hammer Type QBGFEP.



Class I, Div. 2, Groups A, B, C, D

Class II, Div. 2, Groups E, F, G

Class III